

# BS 4,8 FM APPROVAL

Drill point screw for use in steel deck (0,70 mm t/m 2 x 1,25 mm thick)

For use with BIT-T25.  
Required length: build-up + 20 mm  
Reduces drill point.

#### Approvals

- Sintef technical approval 2516
- ETA approval 08/0285
- FM approval ID-Nr.3034551
- FM approval ID-Nr.3060559



Size (diameter)  
Ø 4,8 mm

Material  
Enduroguard coating,  
15 cycles

Screw  
Torx-25 head  
Reduces drillpoint

Length  
From 50 and 300 mm

## Products

PRODUCT CODE	Ø MM X LENGTH MM	PACKAGING
1411758	BS-48050 4,8 x 50	1000/Bucket
1411759	BS-48060 4,8 x 60	1000/Bucket
1411760	BS-48070 4,8 x 70	1000/Bucket
1411761	BS-48080 4,8 x 80	500/Bucket
1411762	BS-48090 4,8 x 90	500/Bucket
1413027	BS-48100 4,8 x 100	500/Bucket
1413028	BS-48110 4,8 x 110	500/Bucket
1413029	BS-48120 4,8 x 120	500/Bucket
1413030	BS-48130 4,8 x 130	500/Bucket
1413031	BS-48140 4,8 x 140	500/Bucket
1413032	BS-48150 4,8 x 150	500/Bucket
1413033	BS-48170 4,8 x 170	500/Bucket
1413034	BS-48190 4,8 x 190	500/Bucket
1413035	BS-48200 4,8 x 200	500/Bucket
1413036	BS-48220 4,8 x 220	500/Bucket
1413037	BS-48240 4,8 x 240	500/Bucket

## Products

PRODUCT CODE	Ø MM X LENGTH MM	PACKAGING
1413038	BS-48260 4,8 x 260	500/Bucket
1413039	BS-48280 4,8 x 280	500/Bucket
1413040	BS-48300 4,8 x 300	500/Bucket

## Associated products

